

## STAFF REPORT

17995Item 1 of 2

**Property Location:** 434 Chautauqua  
Chautauqua Historic District

**Applicants:** Krittenbrink Architecture LLC  
On behalf of owners Kash and Nina Barker  
434 Chautauqua

**Request:**

- Remove dormer peaks on front elevation
- Continue existing mansard roof with wood shingle siding on second floor in a single plane the full width of the house
- Remove front porch screens, screen door and partial porch walls and replacing with railing and baluster system and piers with tapered cedar columns

**Background:** This contributing, two-story Craftsman/Bungalow-style structure was built around 1920. The exterior walls are a combination of weatherboard and wood shingle. The structure has a decorative concrete block foundation. The asphalt-shingle, side gambrel roof is cross-gabled. Wood windows are predominantly vertical, four-over-one, hung. The wood front door is glazed and paneled. The partial porch has been screened. Decorative details include sets of triple windows.

**Guideline References:** The *Historic Preservation Handbook* addresses the proposed changes in the following sections:

**Section 1.4 *Secretary of the Interior Standards for Rehabilitation***

**4. *Acknowledge Changes Over Time.*** Most properties change over time; those changes that have acquired historic significance in their own right shall be retained and preserved.

**Section 3.1 Guidelines for Exterior Walls**

**.1 *Preserve Original Walls.*** Retain and preserve exterior walls that contribute to the overall historic form and character of a building, including functional and decorative features and details.

**.2 *Retain Original Building Materials.*** Retain and preserve exterior wall materials that contribute to the overall historic

## STAFF REPORT

character of a building.

**Section 3.2 Guidelines for Wood Features**

**.1 Preserve Original Features.** Retain and preserve wood features that contribute to the overall historic character of a building, including siding, shingles, cornices, brackets, pediments, columns, balustrades and architectural trim.

**Section 3.6 Entrances, Porches and Balconies**

**.1 Preserve Original Entrances, Porches and Balconies.** Retain and preserve entrances, porches and balconies that contribute to the overall historic character of a building, including column, pilasters, piers, entablatures, sidelights, fanlights, transoms, steps, railings, floors and ceilings.

**Staff Comment:**

The applicants were granted a COA at the March 3, 2014 meeting to allow the removal of a two-story, non-original rear addition which will be replaced with a new rear addition in the same footprint; to rebuild a rear deck and staircase, and relocate existing windows on the north elevation in order to facilitate interior programming. Building permits are currently being reviewed to begin this work.

With this application they are seeking a COA to modify the front elevation of the house including the front porch and the front wall of the second story. These are both areas they believe have been altered from the house's original form and several of these modifications have resulted in deterioration related to poor drainage and have attracted critters. The owners seek to solve both drainage and wildlife issues in a manner that still preserves the major character-defining features of the front of the house.

**Front Porch**

The existing front porch consists of partial walls on the east and south sides covered with wood siding. The porch roof is supported by square piers on north and south corners which are faced with weatherboard siding of a similar profile found elsewhere on the house. The screened porch includes a centered, wood panel screen door. The porch is accessed by a brick walkway and a set of centrally located brick steps with iron handrails.

## STAFF REPORT

*Proposed Changes*

As a way to make the porch feel less closed in and to allow the house to better embrace the street, the applicants propose to remove porch screening and screen door and reduce by half the size of existing wood piers on north and south corners, adding tapered cedar columns to support the roof. Wood siding would remain on the remaining piers. Front steps remain and would be flanked at the porch edge by half-size wood piers. Between piers there would be a wood handrail and baluster system.

*Second Floor Front Wall*

In its current form, the second floor of this structure has a gambrel roof form which is evident on the north and south elevations with a modified mansard roof form on the east elevation. The mansard is covered with wood shingles which continue around to the side gambrels. The mansard includes a pair of small gables with the same pitch as the gambrel over a pair of recessed, triple windows. According to investigation done by the applicants' architect, the gables are decorative and not structural, leading them to deduce that the gables were a later addition. The mansard slopes away from the windows draining onto the porch roof below.

*Proposed Changes*

The applicants propose to remove the two gables peaks on the east elevation, leaving the pair of triple windows intact. In addition they propose to remove the window recesses, creating a continuous mansard roof plane and allowing for more effective guttering and drainage. Deteriorated wood shingles will be replaced in kind.